Prestige electronics

PRODUCTS MADE TO PERFECTION

WINDING RESISTANCE METER



MODEL: PE-18RP DUAL

(FOR DISTRIBUTION TRANSFORMERS, MOTORS, GENERATORS)







FEATURES

- 4.5 Digit Display
- 10 MVA/33 KV to 100 KVA
- Max Test Current 1A
- Fast Response
- Dual Channel
- $1\mu\Omega$ Resolution
- OLTC Measurements
- High Accuracy
- Heat Run Testing

Software

- PC Interface

GENERAL SPECIFICATIONS

- DISPLAY: 4 Line Backlit LCD Display
- POWER: $230V \pm 15\%$, 50/60 Hz
- OPERATING TEMP:5° TO 45° C
- TEMP COEFFICIENT: 50 P.P.M.
- PROTECTION: AGAINST INDUCTIVE BACK EMF/SURGES, OVER TEMPERATURE & POWERFAILURE.

TECHNICAL SPECIFICATIONS

Test Current	Range	Accuracy
I1 (1A)	19.999m Ω , 199.99m Ω , 1.9999 Ω 19.999 Ω	+/- 0,05% of range
I2 (0.1A)	199.99mΩ, 1.9999 Ω , 19.999 Ω , 199.99 Ω	+/- 0.07% of reading except 0.1% of range
I3 (0.01A)	1.9999 Ω , 19.999 Ω , 199.99 Ω, 1.9999 kΩ	+/- 0.07% of reading for 1.9999 kΩ

APPLICATIONS

- DistributionTransformers upto10MVA/ 33KV
- Generators
- Motors
- Live switchyard measurements


ACCESSORIES

- 12m Probe Set
- 4 inch 'C' Clamps
- Crocodile Clip Set
- Instruction Manual
- Mains Cord
- Carrying Case

Carrying Case (Instrument + Probeset)




Probe Set



WE ARE CONDUCTIVE TO RESISTIVE MEASUREMENTS

Heat Run Testing Software PE-WRM 2.0



Prestige electronics

ADDRESS: - 5/265, ASHIRWAD INDL ESTATE, RAM MANDIR

ROAD, GOREGAON (W), MUMBAI: - 400104

TEL/FAX: - 02226763840/02226763911/02266978019

EMAIL: - sales@prestigeelectronics.com WEBSITE: - www.prestigeelectronics.com

WE ARE CONDUCTIVE TO RESISTIVE MEASUREMENTS
